



Code	1500-SCE
Output	6.4kW
Log length	350mm
Nett efficiency	74.4%
Width	508mm
Height	558mm
Depth	407mm

The newly improved, sleek and cutting-edge design of the i Series makes these cassette stoves perfect for the modern, energy-conscious household.

Complete with heat convection system, easy-to-use controls and tertiary burn system, the i Series will get the most from your fuel. Our range of colour finishes will ensure your i Series stove fits perfectly into your home, whilst the internal pre-heated airwash system keeps your glass clear for a warming view of the fire.

Please note: Measurements do not include optional trims as shown

Features

Lifetime guarantee Preheated airwash system for clean glass Stainless steel ash pan Burns wood or solid fuel Optional choice of trim size and colour Optional choice of door colours Radiant and convected heat Patented Flexifuel System Primary and secondary burn to improve efficiency Top flue fitting 127mm (5") Internal flue fitting for ease of installation Approved for use in Smoke Control Areas

Optional Extras

Arada Ash Carrier - Medium - [ARA017] Trim For 1500 3 Sided - Standard (30mm) - [TRIM016] Trim For 1500 4 Sided - Standard (30mm) - [TRIM022] Trim For 1500 4 Sided - Wide (60mm) - [TRIM034] Trim 1500 3 Sided - Wide (60mm) - [TRIM028]



Arada Ltd, The Fireworks, Weycroft Avenue, Axminster, Devon. EX13 5HU. | Tel: +44 (0)1297 35700 (Mon-Fri 8:30am-5pm) Web: http://www.aradastoves.com | Email: info@aradastoves.com Printed 9th June 2017. Technical information updated 27th April 2017.

i500 - Technical Information

Code	1500-SCE
Output range	2-9kW
Nett efficiency	74.4 %
Width	508mm
Height	558mm
Depth	407mm
Width in fireplace	508mm
Height in fireplace	556mm
Depth into fireplace	351mm
Depth of back to centre of top flue	100mm
Flue diameter	127mm
Flue outlet	Vertical Spigot
Suitable for 12mm hearth	No
Under hearth temperature	77.8°C
Suitable for direct air supply kit	No
Packed weight	75kg
Maximum log length	350mm

Please note: Measurements do not include optional trims as shown

Minimum Distance To Combustibles

To sides of stove	150 mm
Above stove	550 mm



Arada Ltd, The Fireworks, Weycroft Avenue, Axminster, Devon. EX13 5HU. | Tel: +44 (0)1297 35700 (Mon-Fri 8:30am-5pm) Web: http://www.aradastoves.com | Email: info@aradastoves.com Printed 9th June 2017. Technical information updated 27th April 2017.