









Code	1600-SCE
Output	7.5kW
Log length	480mm
Nett efficiency	74.4%
Width	609mm
Height	558mm
Depth	407mm

The newly improved, sleek and cutting-edge design of the i Series makes these cassette stoves perfect for the modern, energy-conscious household.

Complete with heat convection system, easy-to-use controls and tertiary burn system, the i Series will get the most from your fuel. Our range of colour finishes will ensure your i Series stove fits perfectly into your home, whilst the internal pre-heated airwash system keeps your glass clear for a warming view of the fire.

Please note: Measurements do not include optional trims as shown

Features

Lifetime guarantee

Preheated airwash system for clean glass

Stainless steel ash pan

Burns wood or solid fuel

Optional choice of trim size and colour

Optional choice of door colours

Radiant and convected heat

Patented Flexifuel System

Primary and secondary burn to improve efficiency

Top flue fitting 127mm (5")

Internal flue fitting for ease of installation

Approved for use in Smoke Control Areas

Optional Extras

Arada Ash Carrier - Large - [ARA018]

Trim For I600 3 Sided - Standard (30mm) - [TRIM017]

Trim For I600 3 Sided - Wide (60mm) - [TRIM029]

Trim For I600 4 Sided - Standard (30mm) - [TRIM023]

Trim For I600 4 Sided - Wide (60mm) - [TRIM035]

i600 - Technical Information

Code	1600-SCE
Output range	2-11kW
Nett efficiency	74.4 %
Width	609mm
Height	558mm
Depth	407mm
Width in fireplace	608mm
Height in fireplace	556mm
Depth into fireplace	351mm
Depth of back to centre of top flue	100mm
Flue diameter	127mm
Flue outlet	Vertical Spigot
Suitable for 12mm hearth	No
Suitable for direct air supply kit	No
Packed weight	88kg
Maximum log length	480mm

Please note: Measurements do not include optional trims as shown

Minimum Distance To Combustibles

To sides of stove	150 mm
Above stove	600 mm

